

New

D500

Defibrillator/Monitor



- Multifunctional Defibrillator/Monitor
- Manual and AED operation
- SpO2 pulse oximetry (Nellcor)
- Non-invasive Pacing Mode
- Efficient Biphasic technology
- Defibrillation with paddles, Pads or Internal paddles
- ECG monitoring



D500 Defibrillator/Monitor



Paddle Type



Defibrillation Mode Selector

Defib Common / AED Mode / Manual Mode

LCD type

ECG & Text display

Shock Button

Flashing button indicates ready for shock delivery. Push the button to deliver shock.

Non-Invasive Pacing

Monophasic Truncated Exponential

Nellcor Oximax SpO2

Pulse Oximetry

Connecting socket

Defibrillator pads connector socket

SD card

Review data stored & software upgrade



D500 Defibrillator / Monitor Specification

Display

Screen Size 170.0*128 (mm) (8.4 in diagonally across the TFT-LCD screen)
Screen Type/Color Liquid Crystal Display (LCD) Color
Resolution 800*600 pixel

Controls

Standard Knob; Mode key (Off, AED, Manual, Pacing); 12 soft buttons (Shock, Select Energy, Charge, Analyze, NIBP, REC, LEAD, Alarm Off, Size, Display, bpm, mA); 5 soft key

Alarms

Categories	Patient Status and System Status
Priorities	Low, Medium and High Priorities
Notification	Audible and Visual
Setting	Default and Individual
Alarm Volume Level	45 to 84 dB

Physical Characteristics and Printer

Instrument

Dimensions	348*256*332 (mm) (W*H*D) including a handle and paddles excluding options and accessories
Weight	Approx. 7.45 kg including paddles excluding optional configurations and accessories
Degree of Protection against Electric Shock	
ECG:	Type CF with defibrillation protection
Respiration:	Type CF with defibrillation protection
SpO2:	Type CF with defibrillation protection
Temperature:	Type CF with defibrillation protection
EtCO2	Type CF with defibrillation protection

Mode of Operation Continuous

Printer

Type	Thermal
Weight	190g
Number of Channels	1 to 3 channels
Paper Width	80 mm
Printer Speed	25 mm/s

Electrical

Instrument

Power Requirement AC Mains 100 to 240 V, 50/60 Hz, 60 to 160 VA

Battery (Option)

Type	Li-ion battery
Voltage	10.8V / 7200mAh
Discharge	A minimum of 100 shocks at 200 Joules (per battery)
Operating Time	5 hours (per battery) At the following condition: no printing, no external communication, no audible alarm sound and room temperature: 25°C
Recharge	7 hours with D500 turned on/off
Dual Battery	Automatic Switching

Environmental Conditions

Operation

Temperature	0 to 40°C (32 to 104°F)
Humidity	15 to 95% RH, non-condensing
Altitude	-170 to 4,877 m (-557 to 16,000 ft)
Water Resistance	IP34

Transport and Storage (in shipping container)

Temperature	-20°C to 50°C (-4°F to 122°F)
Humidity	15 to 95% RH, non-condensing
Altitude	-304 to 6,096m (1,000 to 20,000ft)

Defibrillator

Biphasic Waveform	Biphasic Truncated Exponential
Resuscitation Guidelines	Selectable AHA/ERC

Manual Mode

Shock Energy Level	External Paddles: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 15, 20, 30, 40, 50, 75, 100, 150, 175, 200, 300, 360J
Automatic Discharge Time	60 seconds
Charging Time	Battery: 6 seconds (200J), 10 seconds (360J)
	AC power input: 10 seconds (200J), 15 seconds (360J)
Synchronous Cardioversion	Energy transfer begins within 60msec of the QRS peak

AED Mode

1 ch ECG measurement

Lead	Lead II
Patient Impedance	25 to 175 Ohm
Heart Rate	20 to 300 bpm

Delivered Energy

The D500 delivers shocks to load impedances from 25 to 175 Ohms. The duration of each pulse of the waveform is dynamically adjusted based on delivered charge, in order to compensate for patient impedance variation, as shown below;

Load resistance (Ohm)	Delivered energy (Joule)
25	195
50	190
75	185
100	195
125	190
150	185
175	180

Pacer

Pacing Mode	Demand or non-demand
Pacing rate	30 ppm to 180 ppm
Resolution	2 ppm
Accuracy	± 1.5 ppm
Output current	0 mA to 140 mA
Resolution	2 mA
Accuracy	± 5% or 5 mA
QRS Marker	in the demand mode

ECG

Heart Rate

Measurement Rate	0, 20 to 300 bpm
Resolution	1 bpm
Accuracy	±5 bpm

ECG (Electrocardiograph)

Leads	3 / 5 / 12 Lea Lead I, II, III, aVR, aVL, aVF, V1, V2, V3, V4, V5, V6, Paddles, Pads
Lead Off Detection	Detected and displayed
Pads Off Detection	Detected and displayed
Pacer Detection	Detected pacer pulses of ±2mV to ±700mV with pulse widths of 0.1 to 2msec and rise times 10% of width not to exceed 100msec

Input;

Input Impedance	5 M Ohm or more
Input Dynamic Range	±5mV AC, ±300mV DC
Voltage Range	±0.5mV ~ ±5mV
Signal Width	40 to 120 ms (Q to S)

Output (Frequency Response);

Monitoring mode	0.4 to 40 Hz
Diagnostic mode	0.05 to 150 Hz
Low-extended mode	0.05 to 40 Hz
Filter mode	1 to 21 Hz
ECG size	Auto, 5.0, 10.0, 15.0, 20.0, 30.0 mm/mV
Display Sweep Speeds	25.0 mm/sec
Display Sensitivity	10 mm/mV
Pacing Pulse Detection	On, Off
Electrode Disconnect Alarm	Display and/or sound
Common Mode Rejection (CMRR)	80 dB or more
Defibrillator Discharge Recovery	less than 5 sec per IEC 60601-2-27
Defibrillation Protection	Protected

Interpretive Algorithm

12-Lead Interpretive Algorithm	University of Glasgow 12-Lead ECG Analysis Program
--------------------------------	--

Respiration

IM Respiration

Technique	Impedance Pneumography
Range	0, 3 to 120 breaths/min
Resolution	1 breaths/min
Leads	RA to LA
Base impedance	500 to 2000 ohm
Delta impedance	0.5 to 3 ohm
Lead Off Condition	Detected and displayed
Defibrillator Protection	Protected

AW Respiration

Technique	Non-dispersive Infrared Spectroscopy
Range	0 to 120 breaths/min
Accuracy	±1 breaths/min
Display Sweep Speeds	12.5 mm/sec

NIBP

Pulse Rate

Pulse Rate Range	Adult/Pediatric	40 to 200 bpm
	Neonatal	40 to 240 bpm
Resolution		5 bpm

NIBP (Non-Invasive Blood Pressure)

Technique	Oscillometric Measurement	
Measurement Modes	Off, cont, 1, 2.5, 3, 5, 10, 15, 30, 60, 90 minutes	
Measurement Range	Adult/Pediatric	

SYS	60 to 250mmHg
MAP	45 to 235mmHg
DIA	40 to 200mmHg

Neonatal

SYS	40 to 120mmHg
MAP	30 to 100mmHg
DIA	20 to 90mmHg

NIBP Accuracy	Mean error and standard deviation per ANSI/AAMI SP10:2002+A1:2003+A2:2006	
---------------	---	--

Pressure Display Range	Adult/Pediatric	0 to 300 mmHg
	Neonatal	0 to 150 mmHg

Pressure Display Accuracy	Adult/Pediatric	±10mmHg
	Neonatal	±5mmHg

Initial Cuff Inflate Pressure	Adult/Pediatric	120, 140, 160, 180, 200, 220, 240, 260, 280mmHg
	Neonatal	80, 90, 100, 110, 120, 130, 140 mmHg

Automatic Cuff Protector	Adult/Pediatric:	300 mmHg
	Neonatal:	150 mmHg

Defibrillator Protection	Protected	
--------------------------	-----------	--

Measurement Speed	About 20 seconds	
-------------------	------------------	--

IBP

Pulse Rate

Pulse Rate Range	20 to 250 bpm
Pulse Rate Resolution	1 bpm

IBP (Invasive Blood Pressure)

Parameter Displayed	P1, ABP P2, CVP, PAP, LAP
Measurement Range	-50 mmHg to 300 mmHg 20 bpm to 250 bpm

Resolution	1 mmHg
Input Sensitivity	5 μ V/mmHg
Transducer Volume Displacement	0.1 mm ³ /100 mmHg
Zero Calibration Range	± 100 mmHg
Frequency Response	25 Hz
Wave Size	0 to 20, 0 to 50, 0 to 100, 0 to 200, 0 to 300, Auto Size

Display Sweep Speeds	25.0 mm/s
----------------------	-----------

Defibrillator Protection	Protected
--------------------------	-----------

SpO2

%Saturation

Range	0% to 100%
Perfusion Range	0.03% to 20 %
Accuracy Adults ¹	70% to 100% ±2 digits
Neonate	70% to 100% ±2 digits
Low Perfusion ²	70% to 100% ±2 digits
Display Sweep Speeds C-Lock	12.5mm/sec, 25.0mm/sec & 50.0mm/sec

Pulse Rate

Pulse Rate Range	25 to 240 bpm
Resolution	1 bpm
Accuracy	No motion: ± 3 bpm Motion: ± 5 bpm

Asystole Detection Time	± 8 sec
-------------------------	---------

Delay	± 10 sec
-------	----------

Response Time	± 20 sec
---------------	----------

1. Adult specifications are shown for OXIMAX MAX-A and MAX-N sensors with the D500. Neonate specifications are shown for OXIMAX MAX-N sensors with the D500. Saturation accuracy will vary by sensor type.
2. Specification applies to the D500 performance. Reading accuracy in the presence using signals supplied by a patient simulator. SpO2 and pulse rate values were varied across the monitoring range including weak signal conditions and compared to the known true saturation and pulse rate of the input signals.

Capnography

Display	EtCO ₂ , InCO ₂
Range	0 to 150 mmHg
Accuracy	0 to 40 mmHg ±2 mmHg of reading 41 to 70 mmHg ±5% of reading 71 to 100 mmHg ±8% of reading 101 to 150 mmHg ±10% of reading

Display Accuracy	±2 mmHg
Response Time	Mainstream: Less than 60ms Sidestream: Less than 3sec
Gas Compensation	User selective at O ₂ > 60% and N ₂ O > 50%
Warm Up time	2 minutes maximum
Sound Noise Level	Less than 41dB when ambient sound pressure level is 22dB
Sweep Speeds	6.25mm/sec, 12.5 mm/sec and 25.0 mm/sec

Temperature

Probe Types	Thermistor probe
Parameter displayed	TEMP1, TEMP2
Range	15°C to 45°C (59°F to 113°F)
Display Accuracy	±0.1°C (25°C to 45°C) or ±0.2°F (77°F to 113°F) ±0.2°C (15°C to less than 25°C) Or ±0.4°C (59°F to less than 77°F)

Event

Date	12 lead, Events
Memory	Saves total 100 data (12 lead) Total 250 date (events) Saves date and time Saves alarm condition Saves HR/PR, NIBP, SpO ₂ , Temp, IBP1, IBP2, EtCO ₂ numeric data Saves ECG, EtCO ₂ , 2 channel IBP waveform data
Removable Memory	SD Card/USB

Optional Items

Non-invasive Blood Pressure with cuffs and cuff hoses
SpO₂ (Nellcor) with DS-100A and DOC-10
12 Lead ECG with Interpretation from the University of Glasgow
Continuous Temperature Monitoring
EtCO₂, selectable either Mainstream or Sidestream from Respirationics
Invasive Blood Pressure Monitoring (2 lines)
Wi-Fi/3G Communication module
Wireless LAN data transmission
Additional Battery



Mediana Seoul office

Mediana Building, #793-3, Bangbae-dong,
Seocho-ku, Seoul, Korea (P.C: 137-830)
Tel : +82-2-542-3375 Fax : +82-2-542-7447

Mediana Head office / Factory / R&D

Wonju Medical Industry park, #1650-1, Donghwa-ri,
Munmak-eup, Wonju-si, Gangwon-do, Korea (P.C : 220-801)
Tel : +82-33-742-5400 Fax : +82-33-742-5418

www.mediana.co.kr



Mediana US Company

5850 Farinon Drive, San Antonio, Texas 78249 U.S.A.
Tel : 800-829-6427 (NIBP)
Tel : +1-210-690-6200 Fax : 1-210-696-8808

www.medianatech.com